

# ThinkCentre Tiny-in-One (TIO) 22 Gen3

Product Specifications Reference (PSREF)

Model	<i>Non-touch model:</i> 10R1PAR1++/10R1PAT1++; <i>Touch model:</i> 10R0PAR1++/10R0PAT1++			Mounting features	Wall or desk mounting using the extend arm or third-party accessories meeting the VESA FPMPI® (100mm mount)																				
Form factor	Tiny-in-One, offers a full All-In-One experience when optional Tiny slots into the back of TIO, clean cabling and effortless setup			Adjustable stand	<i>Tilt:</i> 30° back, -5° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°; <i>Pivot:</i> clockwise 0° to 90°																				
Compatible Tiny:	M910 / M710 / M900 / M700 / M600 / M715 / M93/p* / M83 / M73* / M53 / Chromebox Tiny * Non-TIO models can't be turned on by pressing power button of TIO			Power supply	90 watts AC/DC adapter, 88% PSU, universal																				
Panel	TFT-LCD, In-Plane Switching technology**, White LED backlight <i>Notes:</i> In-Plane Switching may refer to VA, PLS, and IPS panels			Power consumption	19 watts typical, 32 watts maximum, <0.5 watts standby / suspend																				
Viewable image size	21.5" (546.1mm) diagonal			Limited warranty	<b>3-years</b> , Customer Carry-In or Mail-In via Rapid Replacement Service																				
Max view area (W x H)	18.74" x 10.54" / 476.1mm x 267.8mm			VESA-compliant	VESA DDC2B/CI, VESA DPMS-compliant																				
Bezel Width	Top / Side: 2mm, Bottom: 22.1mm			Ergonomics	ISO 9241-307, TUV Eye Comfort certified																				
Native resolution	<b>1920x1080</b>			Emission standards	FCC Class B																				
Multi-touch	Optional 10-point multi-touch, supports Wake on Touch			Environmental	TCO 7.0, TCO Edge 2.0, WEEE, RoHS, ENERGY STAR® 7.0, EPEAT™ Gold rating, ULE Gold, TUV, VOC																				
Aspect ratio	16:9			Windows certifications	Windows 7 and Windows 10 certified																				
Pixel pitch (mm)	0.24795mm			Ship group	TIO (Monitor), detachable stand, AC/DC power adapter, power cord, user's guide and driver CD, quick start and safety poster																				
Dot/Pixel per Inch	102.4 dpi			Accessories	For compatible accessories, please go to <a href="http://www.lenovoquickpick.com">http://www.lenovoquickpick.com</a>																				
Brightness	250 nits or cd/m² (typical)																								
Contrast ratio	1000:1 (typical)																								
Pixel response time	14ms (default), over drive to 4ms, 6ms																								
Color gamut	72%																								
Anti-reflective	Anti-glare																								
Viewing angle at 10:1 CR	178° (+/- 89°) horizontal, 178° (+/- 89°) vertical																								
Preset resolutions	640x350 @ 70Hz 640x480 @ 60Hz, 66Hz, 72Hz, 75Hz 720x400 @ 70Hz 800x600 @ 60Hz, 72Hz, 75Hz 1024x768 @ 60Hz, 70Hz, 75Hz 1152x864 @ 75Hz 1280x800 @ 60Hz 1280x1024 @ 60Hz, 72Hz, 75Hz 1366x768 @ 60Hz 1440x900 @ 60Hz, 75Hz 1600x1200 @ 60Hz, 70Hz, 75Hz 1680x1050 @ 60Hz 1920x1080 @ 60Hz																								
Presets / user settings	Presets: 25; user settings: 25																								
On screen display	On screen display with digital user controls (8 languages)																								
Control features	<i>Front:</i> Exit button, Left / Mode-switching button (TIO / monitor mode), Right / Brightness button, Enter / Menu button, Power button <i>Bottom:</i> Volume up button, Volume down button																								
Tiny-in-One Power On	Pressing Alt + P on keyboard or pressing Power button positioned on TIO can turn on both TIO and Tiny (only some Tiny support, see compatible list)																								
Side ports (TIO)	One USB 3.1 Gen1 / USB 2.0 (when M73 or M53 installed or USB 2.0 connected via USB upstream port) <i>Notes:</i> The USB port is only available when a Tiny is installed or a PC is connected via USB upstream port																								
Side ports (Tiny)	Side ports offered by installed Tiny (optional)																								
Rear ports	One DisplayPort in port, one USB upstream port, one power connector																								
3-in-1 Cable	Undetachable 3-in-1 cable (Power connector, USB [supports USB 3.1 Gen1 / USB 2.0], DisplayPort), only for connecting to Tiny installed (optional)																								
Camera	720p camera with dual microphone for VOIP, LED indicator																								
Internal Speaker	2 watt x2																								
Security	Security keyhole for attachment of optional cable lock (Kensington® lock compatible), locks optional Tiny with TIO together, more security features offered by Tiny installed (optional)																								
Mechanical	<table border="1"> <thead> <tr> <th></th> <th>Dimensions</th> <th>TIO without stand</th> <th colspan="2">TIO with stand</th> </tr> </thead> <tbody> <tr> <td>W x D x H (inch)</td> <td></td> <td>19.26 x 2.85 x 13.35</td> <td colspan="2">19.26 x 10.76 x 14.59 - 18.93</td> </tr> <tr> <td>W x D x H (mm)</td> <td></td> <td>489.3 x 72.5 x 339</td> <td colspan="2">489.3 x 273.3 x 370.7 - 480.7</td> </tr> <tr> <td>Weight (Approx.)</td> <td></td> <td>7.01 lb / 3.19 kg</td> <td colspan="2">11.77 lb / 5.34 kg</td> </tr> </tbody> </table>						Dimensions	TIO without stand	TIO with stand		W x D x H (inch)		19.26 x 2.85 x 13.35	19.26 x 10.76 x 14.59 - 18.93		W x D x H (mm)		489.3 x 72.5 x 339	489.3 x 273.3 x 370.7 - 480.7		Weight (Approx.)		7.01 lb / 3.19 kg	11.77 lb / 5.34 kg	
	Dimensions	TIO without stand	TIO with stand																						
W x D x H (inch)		19.26 x 2.85 x 13.35	19.26 x 10.76 x 14.59 - 18.93																						
W x D x H (mm)		489.3 x 72.5 x 339	489.3 x 273.3 x 370.7 - 480.7																						
Weight (Approx.)		7.01 lb / 3.19 kg	11.77 lb / 5.34 kg																						

ThinkCentre Tiny-in-One 22 Gen3 Compatible list			
Model	M910 / M710 / M900 / M700 / M600 / M715 / M83 / M53 Tiny	M93/p Tiny, M73 Tiny	Chromebox
Turn on TIO and Tiny together via Alt + P on USB KB	All models	All models	Not support
Turn on TIO and Tiny together via TIO Power Button	All models	TIO models	All models