ThinkCentre M93/M93p Tower Platform Specifications

Processor	4th Congretion	Intol® Co	roTM i2 / i5 / i7 Drocco	corc			Managoshility	Intel Active Management Technology 9.0 (Intel AMT 9.0)		
Processor		Cores /	re™ i3 / i5 / i7 Proces Frequency			Integrated	Security chip	Trusted Platform Module, TCG 1.2-compliant		
	Processor	Threads	(Base/Max)	Cache	Memory Types	Graphics		 One lock to secure both cover and entire system to fixed object: Administrator password Hard disk password 		
	Core i3-4130	2/4	3.4 GHz	3 MB	DDR3-1600	HD 4400				
	Core i5-4570	4/4	3.2 GHz / 3.6 GHz	6 MB	DDR3-1600	HD 4600		-Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Boot sequence control Boot without keyboard and mouse		
	Core i5-4590	4/4	3.3 GHz / 3.7 GHz	6 MB	DDR3-1600	HD 4600		Kensington® MicroSaver® cable) • Individual USB port disablement		
	Core i5-4670	4/4	3.4 GHz / 3.8 GHz	6 MB	DDR3-1600	HD 4600		Power-on password Optional Chassis intrusion switch		
	Core i7-4770	4/8	3.4 GHz / 3.9 GHz	8 MB	DDR3-1600	HD 4600	Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo logo		
	Core i7-4790	4/8	3.6 GHz / 4 GHz	8 MB	DDR3-1600	HD 4600	Mouse	Enhanced Optical USB Mouse, black, Lenovo logo		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets						Mechanical	 Mini Tower (25L), business black color, metal case (WxDxH) 6.89" X 17.41" X 16.32"; 175mm X 442.3mm X 414.5mm 		
Optical Onboard SATA Media reader Graphics	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm Some: 500GB (5400 rpm, 2.5" wide) or 1TB (7200 rpm, 3.5" wide) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide Some: DVD-ROM SATA 1.5Gb/s Drive Some: Super Multi-Burner DVD±RW SATA 1.5Gb/s Drive Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s) Optional 29-in-1 media reader, internal USB 2.0 Intel HD Graphics 4400/4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays, works along with discrete graphics to support five independent monitors;					wide ors, <® 11,		24.69 lb (11.20 kg) in maximum configuration Toolless cover removal, adapter retention Toolless disk, optical drive removal Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk Slot 1: half-length, full-height, PCle 3.0 x16 (75w max) Slot 2: half-length, full-height, PCle 2.0 x1 Slot 3: half-length, full-height, PCle 2.0 x16 (x4 elec, 75w max) Slot 4: half-length, full-height, 32-bit PCl 2.3		
	Maximum resol	Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)					Power supply 280 watts, autosensing, 85% PSU			
	Some: AMD Radeon HD 8570, DirectX 11, 3D Hardware Acceleration, 2GB, PCI Express 3.0 x16 adapter (8x elec), one VGA, one HDMI, 40 watt Max resolution: 4096x2160 (HDMI)@24Hz; 2048x1536 (VGA)@85Hz Some: AMD Radeon™ HD 8470, DirectX 11, 3D Hardware Acceleration,				are Acceleration, e VGA, one HDN 8x1536 (VGA)@	85Hz	Limited warranty	Some: 3-years, limited onsite service / service upgrades available Some: 3-years, limited onsite service, IWS (International Warranty Service) / service upgrades available For Lenovo service upgrade options, please go to S-TC sheet		
DP cable	512MB, PCI Express® 2.0 x16 adapter, one VGA, one DisplayPort, 25 watts, Max resolution: 2560x1600 (DisplayPort) @ 60Hz; 2048x1536 (VGA) @ 85Hz Some: AMD Radeon™ HD 7450, DirectX 11, 1GB, PCI Express 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; Max resolution: 2560x1600 (DisplayPort, DVI-I) @ 60Hz Some: NVIDIA® Geforce® GT 620, DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; Max resolution: 2560x1600 (DisplayPort) @ 60Hz; 2048x1536 (VGA) @ 85Hz None					GA)@85Hz 6 adapter, tts; on, 80 watts;	Preload	Preloaded operating system Some: No operating system Windows® 7 Professional 32 Some: Windows 7 Professional 64 Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Windows 7 Professional 64 preinstalled through downgrade Freloaded applications (only some listed) ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Util		
Chipset	Intel Q87 Chipset						-	rights in Windows 8.1 Pro 64-bit ● Desktop Power Manager		
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm),						-	 View Management Utility Lenovo Cloud Storage by SugarSync 		
Rear ports Rear audio ports IEEE 1394	headphone (stereo, 3.5mm) Four USB 3.0, two USB 2.0, serial (9-pin), optional 2nd serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), one VGA, two DisplayPort, optional PS/2 ports (keyboard/mouse), additional VGA, DisplayPort, or HDMI on optional graphic card on some models					models		Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded;		
Audio support	High Definition	(HD) Auc	lio, Realtek ALC662 /	optional i	nternal speaker	(1watt)]	purchase a product key to activate		
WLAN ¹³	Some: 11b/g/n, PCle Half Mini Card, Realtek RTL8723BE, Wi-Fi/BT 4.0, 1x1 Some: 11b/g/n, PCle Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 Some: 11b/g/n, PCle Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2 Some: 11a/b/g/n, PCle Half Mini Card, Intel Centrino Advanced-N 6235, Wi-Fi + Bluetooth combo adapter, 2x2 Some: 11b/g/n, PCle Half Mini Card, Intel Wireless-N 7260, Wi-Fi/BT 4.0, 2x2					c1 5,		 Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro 		
Pluotooth™	Some: 11ac/a/i Wi-Fi +	ome: 110/g/n, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fr/B1 4.0, 2x2 ome: 11ac/a/b/g/n, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo adapter, 2x2 ome: Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter					Environment	ENERGY STAR® 6.0 (Need 85% PSU and Windows OS); EPEAT™ Gold rating (Need 85% PSU and Windows OS); GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; ULE Gold		
Bluetooth™ Ethernet Modem	One gigabit eth	ernet por	reiess, integrated in w t, Intel I217-LM (Clarl	ville), Wa	ake on LAN®	uapter	Accessories	For compatible accessories, please go to TC-AQP sheet		